


Dakota Stone[™]

Step by step instructions for assembling FPS-5228 on a prepared surface/base.

BUILD WITH DAKOTA





Tools Needed:

Dead Blow Hammer Hammer Caulk Gun 4 Foot Level Torpedo Level Square 2 Ladders (6ft min.) This set of instructions assumes you are building on a level grade on a level foundation.

When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot level and check often. Starting on a level foundation is key. When gluing blocks together, be sure not to use too much adhesive - this will cause the blocks to "swim." A small bead is ideal.

Dakota StoneTM

BUILD WITH DAKOTA

FPS-5228

Standard Fireplace


			REVISIONS
		MM/DD/YY	REMARKS
-	1	03/03/15	Total Rewrite in new style with color. TP
	2	06/04/15	2 SKU and QR update
	3	//	
	4	//	
	5	//	

Tools needed

All sizes in this document are approximate.


Square Foot Unit

The "Square Foot Unit." consists of three block as shown. By rotating this unit (SFU) we are able to build quickly and easily while keeping bond lines broken up. These will always be shown in a tan color.




Long Halves are simply made by cutting a block along its center on the longest axis.


Unit Size Color Key




Sometimes SFUs are broken up or can't be used. The Double Unit is the next preferred unit. Double Units are grouped for strength and speed in construction. They are always represented in green.



Cutting four inches off the short end of a Dakota Stone will get you a Third block (and a Square one).



The Single Unit is the basis for all the construction, of course. When used in a single or non-standard configuration, you will see Dakota Stone™ depicted in red.



Cutting four inches off the short end of a Dakota Stone will get you a Square block (and a Third one).

Dakota Stone^{rm}


BUILD WITH DAKOTA

FPS-5228

		REVISIONS
	MM/DD/YY	REMARKS
1	03/03/15	Total Rewrite in new style with color. TP
2	06/04/15	2 SKU and QR update
3	//	
4	//	
5	//	


All sizes in this document are approximate.

Unit Size Color Key




12" x 12" Ledge Rock paver.


Great to use as a large cap. Always shown in dark blue.




6" x 12" Ledge Rock paver. Great to use as a cap. Always shown in middle blue.




6" x 9" Ledge Rock paver. Great to use as a small cap. Always shown in light blue.



6" x 6" Ledge Rock paver. Great to use as a cap. Always shown in dark blue.



Lintel Block. There are two precision cut lintel block in your kit. They will be untumbled. "Age" the edges with a hammer before installing.



Fire brick. These hard refractory brick are very dense. Use them to line your firebox. Three come cut to a narrower width.

BUILD WITH DAKOTA


Standard Fireplace


	REVISIONS				
	MM/DD/YY	REMARKS			
1	03/03/15	Total Rewrite in new style with color. TP			
2	06/04/15	2 SKU and QR update			
3	//				
4	//				
5	//				

When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot level and check often. Starting on a level foundation is key. When gluing blocks together, be sure not to use too much adhesive - this will cause

When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot evel and check often. Starting on a level

This is your foundation block. One cannot over emphasize the importance of properly installing this layer. Be sure to take the time to ensure it is "perfectly" square and level. Any imperfections here will continue to show up over and over as you build this kit.






BUI	LD	W	IT	Ή
D	AK	OT	Ά	


F	P	S	-5	2	2	8	

			REVISIONS
		MM/DD/YY	REMARKS
_	1	03/03/15	Total Rewrite in new style with color. TP
	2	06/04/15	2 SKU and QR update
	3	//	
	4	//	
	5	//	


Consider not gluing these central block of the fire box floor (depicted by the darker shaded block). They will be much easier to flip over or replace if needed down the road.



FRONT



The entire back of the fire-place is flush. There are no setbacks. Be sure to keep your fireplace plumb as you build. Use your 4' level and check often.



BUILD WITH DAKOTA

FPS-5228	
-----------------	--


Standard Fireplace

	REVISIONS				
	MM/DD/YY	REMARKS			
1	03/03/15	Total Rewrite in new style with color. TP			
2	06/04/15	2 SKU and QR update			
3	//				
4	//				
5	//_				




The entire back of the fireplace is flush. There are no set-backs. This should aid in keeping your fireplace plumb as you build.

Always start building from the outside corners. This will help ensure you keep your structure plumb.



Any time you see a block with just the wide top showing, fret not, it is a Square Foot Unit (SFU). The unit is just turned where the that is the only block you see.




12"

BUILD WITH DAKOTA

FPS-5228

Standard Fireplace

			REVISIONS
		MM/DD/YY	REMARKS
	1	03/03/15	Total Rewrite in new style with color. TP
	2	06/04/15	2 SKU and QR update
	3	//	
	4	//	
	5	//	





FPS-5228

Standard Fireplace

			REVISIONS
		MM/DD/YY	REMARKS
	1	03/03/15	Total Rewrite in new style with color. TP
	2	06/04/15	2 SKU and QR update
	3	//	
	4	//	
	5	//	

Always build the side walls of your fire box first. Start where the brick are denoted with an asterisk (*). Abut the fire brick to the front blocks and work toward the rear wall. Then lay the back wall. The side walls will pass the face of the back wall. Do not fill the air gap in the corner. Only glue the back of the fire brick to the block behind them. Do not glue the fire brick to each other. Follow this procedure for the entire fire box.






BUILD WITH DAKOTA


FPS-5228

Standard Fireplace

			REVISIONS
		MM/DD/YY	REMARKS
	1	03/03/15	Total Rewrite in new style with color. TP
	2	06/04/15	2 SKU and QR update
	3	//	
	4	//	
	5	//	

When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot level and check often. Starting on a level foundation is key. When gluing blocks together, be sure not to use too much adhesive - this will cause






The entire back of the fireplace is flush. There are no set-backs. This should aid in keeping your fireplace plumb as you build.

BUILD WITH DAKOTA


FPS-5228			REVISIONS
FF3-3220		MM/DD/YY	REMARKS
	1	03/03/15	Total Rewrite in new style with color. TP
	2	06/04/15	2 SKU and QR update
Standard Fireplace	3	//	
Staridara i ircpiace	4	//	




Lintel Block with notches. Remember to chip the edges of the block with a hammer to give it an "aged" look. You only need to do this on the side opposite the notch. This will be the 8x4" side that is visible on the outside.



Lintel Block with notches. Be certain to face the notch cuts inward toward the fire box.





chip

this side

BUILD WITH DAKOTA

chip


this side


FPS-5228

Standard Fireplace

	REVISIONS		
	MM/DD/YY	REMARKS	
1	03/03/15	Total Rewrite in new style with color. TP	
2	06/04/15	2 SKU and QR update	
3	//		
4	//		
5	/_/_		

Always build the side walls of your fire box first. Start where the brick are denoted with an asterisk (*). Abut the fire brick to the front blocks and work toward the rear wall. Then lay the back wall. The side walls will pass the face of the back wall. Do not fill the air gap in the corner. Only glue the back of the fire brick to the block behind them. Do not glue the fire brick to each other. Follow this procedure for the entire fire box.






BUILD WITH DAKOTA


FPS-5228


Standard Fireplace

	REVISIONS		
	MM/DD/YY	REMARKS	
1	03/03/15	Total Rewrite in new style with color. TP	
2	06/04/15	2 SKU and QR update	
3	//		
4	//		
5	//		



Place the angle iron such that the top of the angle leg is flush with the top of the lintel blocks. You may need to use coins as shims or add sand under the angle iron to make it flush. Be sure to roughly center the iron to the fire box opening. There will be extra room to allow for the angle iron to expand.







BUILD WITH DAKOTA FPS-5228

Standard Fireplace

	REVISIONS		
	MM/DD/YY	REMARKS	
1	03/03/15	Total Rewrite in new style with color. TP	
2	06/04/15	2 SKU and QR update	
3	//		
4	//		
5	//		

Always start building from the outside corners. This will help ensure you keep your structure plumb.






The entire back of the fireplace is flush. There are no set-backs. This should aid in keeping your fireplace plumb as you build.


BUILD WITH DAKOTA

FPS-5228

		REVISIONS
	MM/DD/YY	REMARKS
1	03/03/15	Total Rewrite in new style with color. TP
2	06/04/15	2 SKU and QR update
3	//	
4	//	
5	//	




FPS-5228
Standard Fireplace



FPS-5228

Standard Fireplace

		REVISIONS
	MM/DD/YY	REMARKS
1	03/03/15	Total Rewrite in new style with color. TP
2	06/04/15	2 SKU and QR update
3	//	
4	//	
5	//	




FPS-5228

Standard Fireplace

	REVISIONS		
		MM/DD/YY	REMARKS
_	1	03/03/15	Total Rewrite in new style with color. TP
	2	06/04/15	2 SKU and QR update
	3	//	
	4	//	
	5	//	

You will need to set up TEMPORARY support blocks before proceeding to the next step.

DO NOT GLUE THESE SUPPORT BLOCKS!



When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot level and check often. Starting on a level foundation is key. When gluing blocks together, be sure not to use too much adhesive - this will cause the blocks to "swim." A small bead is ideal.

BUILD WITH **DAKOTA**


FPS-5228


Standard Fireplace


		REVISIONS		
		MM/DD/YY	REMARKS	
_	1	03/03/15	Total Rewrite in new style with color. TP	
	2	06/04/15	2 SKU and QR update	
	3	//		
	4	//		
	5	//		

Be sure to just catch the corner of the support block. It will be easier to remove later.

DO NOT GLUE THESE SUPPORT BLOCKS!







When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot

level and check often. Starting on a level foundation is key. When gluing blocks together, be sure not to use too much adhesive - this will cause

BUILD WITH **DAKOTA**


FPS-5228


Standard Fireplace


REVISIONS MM/DD/YY REMARKS 03/03/15 Total Rewrite in new style with color. TP 2 SKU and QR update

Be sure to just catch the corner of the support block. It will be easier to remove later.

DO NOT GLUE THESE SUPPORT BLOCKS!







When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot level and check often. Starting on a level foundation is key. When gluing blocks together, be sure not to use too much adhesive - this will cause


BUILD WITH DAKOTA


FPS-5228


Standard Fireplace

REVISIONS MM/DD/YY REMARKS 03/03/15 Total Rewrite in new style with color. TP 2 SKU and QR update

There are only two of these in the kit. Be sure they are not the square block. These are true half block. Be sure you get the right ones.







When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot level and check often. Starting on a level foundation is key. When gluing blocks together, be sure not to use too much adhesive - this will cause

BUILD WITH DAKOTA **FPS-5228**

Standard Fireplace


		REVISIONS		
		MM/DD/YY	REMARKS	
_	1	03/03/15	Total Rewrite in new style with color. TP	
	2	06/04/15	2 SKU and QR update	
	3	//		
	4	//		
	5	//_		

18

★These block tend to want to rock back into the opening. Stack block to hold them into place until you place the next course.


Now is a good time to take a break (lunch).

This will allow the glue to set-up.



Keep the back wall of the fireplace flush. Rack the block in approximately 2" from each side.

4x4x8 Third Block





The back wall is ALWAYS flush.


BUILD WITH DAKOTA

FPS-5228

REVISIONS		
	MM/DD/YY	REMARKS
1	03/03/15	Total Rewrite in new style with color. TP
2	06/04/15	2 SKU and QR update
3	//	
4	//	
5	//	








FPS-5228


	REVISIONS		
		MM/DD/YY	REMARKS
_	1	03/03/15	Total Rewrite in new style with color. TP
	2	06/04/15	2 SKU and QR update
	3	//	
	4	//	
	5	//	

Keep the back wall of the fireplace flush. Rack the block in approximately 2" from each side.





8x8x4 Square Block




BUILD WITH DAKOTA


FPS-5228

Standard Fireplace


REVISIONS		
	MM/DD/YY	REMARKS
1	03/03/15	Total Rewrite in new style with color. TP
2	06/04/15	2 SKU and QR update
3	//	
4	//	
5	/_/_	

Keep the back wall of the fireplace flush. Rack the block in approximately 2" from each side.





4x4x8 Third Block




Remove your support blocks from step 14.

BUILD WITH DAKOTA


DS_5228			
-P3-3228		MM/DD/YY	
	1	03/03/15	Total Re
	2	06/04/15	2 SKU ar


	REVISIONS				
		MM/DD/YY	REMARKS		
_	1	03/03/15	Total Rewrite in new style with color. TP		
	2	06/04/15	2 SKU and QR update		
	3	//			
	4	//			
	5	//_			

Keep the back wall of the fireplace flush. Rack the block in approximately 2" from each side.



Remove your support blocks from step 14.





BUILD WITH DAKOTA


FPS-5228


Standard Fireplace


| REVISIONS | MM/DD/YY | REMARKS | 1 | 03/03/15 | Total Rewrite in new style with color. TP | 2 | 06/04/15 | 2 SKU and QR update | 3 | __/__/_ ... | ... | 4 | __/__/_ ... | ... | ... | 5 | __/__/__ ... | ... | ... | ... |

When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot level and check often. Starting on a level foundation is key. When gluing blocks together, be sure not to use too much adhesive - this will cause

When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot level and check often. Starting on a level foundation is key. When gluing blocks together, be sure not to use too much adhesive - this will cause the blocks to "swim." A small bead is ideal.








Remove your support blocks from step 14.


BUILD WITH DAKOTA

FPS-5228

REVISIONS				
	MM/DD/YY	REMARKS		
1	03/03/15	Total Rewrite in new style with color. TP		
2	06/04/15	2 SKU and QR update		
3	//			
4	//			
5	/_/_			

When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot level and check often. Starting on a level foundation is key. When gluing blocks together, be sure not to use too much adhesive - this will cause the blocks to "swim." A small bead is ideal.






BUILD WITH DAKOTA


FPS-5228


Standard Fireplace

REVISIONS				
	MM/DD/YY	REMARKS		
1	03/03/15	Total Rewrite in new style with color. TP		
2	06/04/15	2 SKU and QR update		
3	//			
4	//			
5	//			

Before gluing the top four blocks in place, TEMPORARILY lay out your crown blocks (blue shades) to ensure you have them properly positioned. **DO NOT GLUE THE CROWN BLOCKS AT THIS TIME.** Only glue the four cap support blocks (depicted in red). You want to pull your support block in about 1/2" to allow extra room when squaring your cap later.







When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot level and check often. Starting on a level foundation is key. When gluing blocks together, be

Ota Stone Trw foundation is key. W


BUILD WITH DAKOTA

FPS-5228


REVISIONS				
	MM/DD/YY	REMARKS		
1	03/03/15	Total Rewrite in new style with color. TP		
2	06/04/15	2 SKU and QR update		
3	//			
4	//			
5	//			

Remove the crown blocks before you install the large cap block.

Allow the adhesive to fully cure before proceed-ing to lay the cap on these supports.




Placing the cap is the hardest part of the entire build. Use ladders and/or scaffolding. You can use the ledges created by the racked block as a "strairway" to move the block up until the final heave.



BUILD WITH DAKOTA


FPS-5228		REVISIONS				
1 F 3-3220		MM/DD/YY	REMARKS			
	1	03/03/15	Total Rewrite in new style with color. TP			
	2	06/04/15	2 SKU and QR update			
Standard Fireplace	3	//				
Staridara i ircpiace	4	//				
	_					


When constructing your project, be sure to keep all blocks level, square, and plumb. Use a four foot



Add the finishing blocks. The back and sides of the crown are identical from one side to the other. Center the mantle blocks.

There will be a slight overhang on the front and sides.





BUILD WITH DAKOTA

FPS-5228


Standard Fireplace



blocks together, be sive - this will cause

and check often. Starting on a level

level and chec foundation is k



BUILD WITH DAKOTA

FPS-5228		
1 F 3-3220		MM/DD
	1	03/03/
	2	06/04,
Standard Fireplace	3	/
Stariaara i ii epiace	4	1

	REVISIONS				
		MM/DD/YY	REMARKS		
_	1	03/03/15	Total Rewrite in new style with color. TP		
	2	06/04/15	2 SKU and QR update		
	3	//			
	4	//			
	5	//			

DEL ((C) O L) C